

FEATURES

- Single Line SIP Phone
- POE 802.3af or Power Adapter
- SIP RFC3261
- DHCP, Static IP, VLAN Tagging
- Web and server-based configuration TFTP, HTTP, HTTPS
- Support Carrier Grade TR069
- Support TCP, UDP, TLS, SRTP
- Up to 10 programmable speed dial keys
- Message Waiting Light and Ringer indicator
- Mute, Hold, Vol+/-, Flash, Redial and Spkr Buttons
- Hearing Aid Compatible handset
- Dial Pad Standard 12-Key DTMF Double-injected keys
- Customizable faceplate area for branding and dialling instructions

SPECIFICATIONS

- Dimensions: L204*W110*H101 (mm)
- Colour: Black
- Handset Cord (extended): 3.66m / 12ft
- Flash Time: 100ms, 300ms, 600ms optional, Standard 600ms
- Message Waiting: Compatible with all major hospitality PABXs
- ISO9001, FCC Part 15 and Part 68, CE, CCC
- Carton Dimensions: L46*W37*H24 (cm)
- Package (set/carton): 12sets/carton
- **The stated information/specifications are subject to change without notice.**



HA62IP-10S, Black



E: marketing@bittelasia.com W: www.bittelasia.com

Bittel Asia Pte Ltd (Singapore): Tel: +65 6692 8034 Fax: +65 6692 8001 A: 10 Raeburn Park #03-01 Singapore 049483
Bittel Asia, Inc. (Philippines): Tel: +632 8893 8909 Fax: +632 8893 8909 Ext 802 A: Makati Corporate Office 28th Floor Cityland Pasong Tamo
Tower U2807, 2210 Chinco Roces Avenue (Pasong Tamo), Makati City, Philippines 1230
Copyright © 2022, Bittel Asia, All Rights Reserved. UNO and Bittel Logo are trademarks of Bittel.